



ANTI WAX ADDITIVE (X01236D)

DESCRIPTION

Exocet® Anti Wax is formulated to improve the cold flow and handling properties of diesel and gas oil.

APPLICATION

Exocet® Anti Wax is typically added at the rate of 1 litre of additive to 1,000 litres of fuel.

The additive must be used as a preventative measure and will not work if the fuel is already waxed.

Fuel-specific tests need to be carried out if a minimum operability temperature is required.

BENEFITS



FEATURES

- Boosts the fuel's resistance to waxing
- Allows operation at colder temperatures than fuel specification
- Inhibits the formation of wax crystals
- Reduces the potential for filter plugging
- Works with maximum allowable FAME contents

EXAMPLE PERFORMANCES

	EN590 DIESEL Summer	EN590 DIESEL Winter	CLASS A2 Gas Oil Summer	CLASS A2 Gas Oil Winter
CFPP* Specification	-5°C	-15°C	-4°C	-15°C
CFPP* with Exocet® Additive	-18°C	-26°C	-19°C	-26°C
Treat rate Additive: Fuel	1:1,000	1:1,000	1:1,000	1:1,000

* Cold Filter Plugging Point (CFPP)

WHEN TO USE

- As a prevention to fuel freezing and 'waxing out'
- Forecast is for temperatures of <-5°C
- At the transition between summer grade fuel and winter grade fuel to ensure full protection
- When winter grade fuel is required all year round

TREATMENT RATIO

1 litre of additive treats 1,000 litres of fuel

All Exocet® branded products are available in a range of sizes to 1,000 litres



ANTI WAX ADDITIVE (X01236D)

A GUIDE TO USING EXOCET® ANTI-WAX

Exocet® Anti-Wax works by changing the shape of wax crystals in fuel, making them smaller, the Anti-Wax additive co-crystallises with the fuel wax crystals as they form when the fuel cools down and therefore must be added before wax crystals appear at around 10°C above the cloud point of the fuel.

Anti-Wax must be added to fuel when it is at a temperature above its cloud point, that is to say before any wax starts to precipitate out of the fuel. The cloud point of summer gas oil and summer diesel is around +3°C and the cloud point of winter gas oil and winter diesel is -5°C.

Exocet® Anti-Wax is formulated by FAST in a solvent system to promote good mixing with diesel and gas oil. The fuel to be treated should be clear and bright with no visible signs of waxing having begun, check a sample

from the tank bottom, as often wax will sink to the bottom of a storage tank. The fuel temperature should be above 6°C in winter and above 10°C in summer. For best results add the Exocet® Anti-Wax into the vessel at the correct dosage, 1L treats 1,000L fuel, then add the fuel to be treated on top. The velocity of the fuel addition will give the fuel and Anti-Wax a thorough mix.

If additive is being added to a full tank of fuel, then the fuel and additive mixture should be recirculated using a pump.

WHEN TO USE

- ◆ As a prevention to fuel freezing and 'waxing out'
- ◆ Forecast is for temperatures of <-5°C
- ◆ At the transition between summer grade fuel and winter grade fuel to ensure full protection
- ◆ When winter grade fuel is required all year round

TREATMENT RATIO

1 litre of additive treats 1,000 litres of fuel

All Exocet® branded products are available in a range of sizes to 1,000 litres