



# PREMIUM HEATING OIL ADDITIVES

Fragranced and Unfragranced

## DESCRIPTION

An additive pack for domestic kerosene (BS2869:C2) that can be used to create a premium grade fuel. It is available with the inclusion of fragrance for use in environments sensitive to fuel odours or where sensory evidence of the premium fuel needs to be demonstrated.

## APPLICATION

This multi-component product guards against fuel degradation, the corrosion of metal storage tanks and associated pipework, the adverse effects of fuel interaction with copper containing fittings and pipework and serves to inhibit the build of deposits in storage tanks.

## BENEFITS



## FEATURES

- ◆ Lowers carbon emissions
- ◆ Stabilises fuel – increases its shelf life
- ◆ Inhibits sludge formation
- ◆ Reduces deposit build up around nozzles and on heat exchanger surfaces
- ◆ Reduces service problems
- ◆ Improves system efficiency
- ◆ Has a fresh fuel fragrance (fragranced version)

## WHEN TO USE

- ◆ Fuel is stored for longer than 4 months
- ◆ Fuel filters plug
- ◆ Burner jets foul quickly
- ◆ Excessive soot deposits in the heat exchange chamber
- ◆ There is a desire to optimise fuel combustion and efficiency
- ◆ When the environment is 'fuel smell' sensitive (fragranced version)

## TREATMENT RATIO

200ml treats 1,000 litres of heating oil

All Exocet® branded products are available in a range of sizes to 1,000 litres